



Technical Data Sheet

Flashtape

HCS2114

HCS2114-02

Product Description

HCS2114 and HCS2114-02 is made of polyester tape backed with a fully pressure silicone adhesive. HCS2114 and HCS2114-02 is commonly used to keep all bagging materials plies in place like peel ply, release film and breathers. HCS2114 and HCS2114-02 is also used to protect tooling parts and some component areas from flash of resin.

Properties

Mode	HCS2114	HCS2114-02
Maximum Cure Temperature	400°F (204°C) Silicone	400°F (204°C) Silicone
Basic	Polyester	Polyester
Color	Green, Blue	Green, Blue
Adhesive	Silicone	Silicone
Tape Thickness	0.025mm (0.001")	0.125mm (0.005") 0.045mm (0.002")
Adhesive Thickness	0.038mm(0.002")	0.035mm (0.001")

Availability and Packaging

Mode	HCS2114	HCS2114-02
Standard Size	1" x 72yd (2.54cm x 65.8m)	2" x 72yd (5.08cm x 65.8m)

Storage

Storage temperature: 71.6°F (22°C)

Notes

Shelf time: 2 years

CORPORATE HEADQUARTERS

480 Andover Park East
Seattle, WA 98188

P: (206) 575-1333

F: (206) 575-0856

info@heatcon.com

www.heatcon.com